

Table with columns: Property, Value, Unit, Description. Rows include: Supplier's name or trade mark (ELICA), Model identifier (E017EXI-022-002), Annual Energy Consumption - AEC hood (68.9 kWh/a), Energy Efficiency Class (B), Fluid Dynamic Efficiency - FDE hood (24.8 %), Fluid Dynamic Efficiency class (B), Light Efficiency - LE hood (52.1 lux/W), Lighting Efficiency Class (A), Grease Filtering Efficiency - GFE hood (65.1 %), Grease Filtering Efficiency class (D), Minimum Air Flow in normal use (255 m³/h), Maximum Air Flow in normal use (550 m³/h), Air Flow at intensive/boost setting (650 m³/h), A-weighted Sound Power Emission at minimum speed (49 dB(A) re 1pW), A-weighted Sound Power Emission at maximum speed (65 dB(A) re 1pW), A-weighted Sound Power Emission at intensive or boost speed (68 dB(A) re 1pW), Power consumption off mode - Po (NA W), Power consumption in standby mode - Ps (0.49 W).

Additional Product Information compliant to commission regulation (EU) No 66/2014 and UK SI 2019 No. 539

Table with columns: Property, Symbol, Value, Unit, Description. Rows include: Time increase factor (f, 1.1), Energy Efficiency Index (EEI hood, 64.6), Measured air flow rate at best efficiency point (QBEP, 350 m³/h), Measured air pressure at best efficiency point (PBEP, 405 Pa), Maximum air flow (Qmax, 650 m³/h), Measured electric power input at best efficiency point (WBEP, 159 W), Nominal power of the lighting system (WL, 7 W), Average illumination of the lighting system on the cooking surface (Emiddle, 365 lux).

